
univex						
	Project	Item Number	Quantity			
Pentagonal Oven			Stone Hearth         Pizza Dome Oven         Models:         DOME39P: Pentagonal pizza oven         DOME47P: Pentagonal pizza oven         DOME51P: Pentagonal pizza oven			
Pizza Oven	<ul> <li>* Comes Standard with Black Iron Walls</li> <li>* Comes Standard with Black Iron Walls</li> <li>* Handmade firebrick pizza oven</li> <li>* Static cooking floor</li> <li>* Pentagonal internal cooking chamber</li> <li>* Insulated and ready to be connected to smoke s</li> <li>* Very well insulated, outside is cool to touch at highest temperature</li> <li>* Standard Accessories:</li> <li>* Iron stand</li> <li>* Thermometer</li> </ul>	ted to smoke stack ol to touch or xhaust internal	<ul> <li>3/8" (.95 cm) NPT gas connection</li> <li>Natural Gas or Propane</li> <li>Natural Gas- 4.0" WC</li> <li>Propane- 10.0" WC</li> </ul>			
Univex Corporation	diamete <b>Optionl Accessories:</b> • Black or customizable exterior - Red brick - Yellow brick - 10 x 10 tiles - Marble - Metal leaves - Mosaic - Stone	er 7 7⁄8" (20cm)	exhaust fan is required by code, it needs to be no more than 200-300 CFM. • One year, on-site parts and labor			
U	Univex Corpor www.Univexcor	<b>p.com</b>   Salem, N	ckingham Rd TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 ates of America INTL FAX: (603)893-1249			

Printed in U.S.A.

REV 1 01/2017



## Stone Hearth Pizza Dome Oven



DOME47P

38.9" (99cm)

39.3" (100cm)

66.9" (170cm)

35.4" (90cm)

35.4" (90m)

59" (150m)

72.8" (185cm)

DOME51P

38.9" (99cm)

43.3" (110cm)


70.8" (180cm)


37.4" (95cm)

38.5" (98cm)

61.4" (156cm)

72.8 (185cm)





Gas

Ove	n Weight
DOME39P	2645.5lbs. (1200Kg)
DOME47P	4850.2lbs. (2200Kg)
DOME51P	5180.9lbs. (2350Kg)
DOME55P	5511.6lbs. (2500Kg)
DOME59P	5952.5lbs. (2700Kg)

DOME39P

37.4" (95cm)

32.6" (83cm)

59" (150cm)

29.9" (76cm)

27.9" (71cm)

47.6" (121cm)

72.8" (185cm)

А

В

С

D

Е

F

Н

Number of Pizzas					
Model	12" Pizzas				
DOME39P	5				
DOME47P	7				
DOME51P	9				
DOME55P	11				
DOME59P	13				

DOME55P

41.7" (106cm)

45.3" (115cm)

74.8" (190cm)

38.9" (99cm)

39.8" (101m)

69.3" (176cm)

72.8" (185cm)

DOME59P

41.7" (106cm)

49.2" (125cm)

78.7" (200cm)

38.9" (99cm)

41.7" (106cm)

70.9" (180cm)

72.8" (185cm)

BTU: DOME39P, DOME47P, DOME51P - 92500 BTU DOME55P, DOME59P - 97500 BTU

Electrical Information (60Hz)				
	Voltage	Phase	Amps	
Standard Voltage	115	1	16	

Minimum clearance away from combustibles from all sides: 6" (15.2cm) Minimum clearance away from combustibles from top: 16" (40.6cm) Please note that standard dry-wall or sheet rock is considered a combustible Built on a non combustible floor with at least 32" (81.3cm) surrounding the oven and at least 40" (101.6cm) in front of the oven Minimum clearance under oven: 31 inches<sup>2</sup> (200cm<sup>2</sup>) Leave enough clearance for someone to service the oven

univex	Univex Corporation www.Univexcorp.com	3 Old Rockingham Rd Salem, NH 03079 United States of America	TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249
Printed in U.S.A.	REV 1 01/2017		LH-900