

WE RAISE THE BAR. WE SET THE STANDARD.

Project Item Number Quantity

Round Rotating Dome Oven * Comes Standard with Black Iron Walls

Rotating Dome Pizza Oven

Models:

- Rotante47: Rotating Dome Pizza Oven
- > Rotante59: Rotating Dome Pizza Oven

Features:

Pizza Oven

Univex Corporation

- 47" Cooking chamber with 39.4" cooking Surface
- 59" Cooking chamber with 55" cooking surface
- Handmade firebrick pizza oven
- Rotating cooking floor
- Round internal cooking chamber
- Insulated and ready to be connected to smoke stack
- Very well insulated, outside is cool to touch at highest temperature
- Full Electronic Control

Standard Accessories:

- Iron stand
- Iron door
- Thermometer
- Stack exhaust internal diameter 7 7/8" (20cm)
- Remote Control

Optionl Accessories:

- Black or customizable exterior
 - Marble
 - Mosaic

Burner Specifications:

- 3/4" (1.9cm) NPT gas connection
- Natural Gas or Propane
- Natural Gas- 4.0" WC
- Propane- 10.0" WC

Venting: Depends on local state code. Recommend a dedicated natural draft flue. If exhaust fan is required by code, it needs to be no more than 200-300 CFM.

Warranty:

One year, on-site parts and labor







Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249





Rotating Dome Pizza Oven

Gas

For installation, forklift must be able to lift 5,000 lbs and have at least 72" forks.

Vent Pipe: 7.87"(200mm)

Drawing	Details		
1	Rotante Dome47RT	Rotante Dome59RT	
H (color)	Height H 185cm 72.83" Length L 165cm 65"	Height H 185cm 72.83" Length L 195cm 76.77"	
	External diameter 165cm 65°	External diameter 195cm 76.77"	
L	Rotante Dome47FT	Rotante Dome59FT	
H	Height H 185cm 72.83"	Height H 185cm 72.83"	
	Length L 205cm 80.7"	Length L 235cm 92.5"	
	Depth D 165cm 65"	Depth D 195cm 76.77"	

*The stand is 28" high

For the Dome59RT, If shipped fully assembled, there must be a minimum of 80" clearance on any doorway, hallway with no obstructions to its final location.

For the Dome47RT, If shipped fully assembled, there must be a minimum of 70" clearance on any doorway, hallway with no obstructions to its final location.

Minimum clearance away from combustibles from all sides: 6" (15.2cm) Minimum clearance away from combustibles from top: 16" (40.6cm)

Please note that standard dry-wall or sheet rock is considered a combustible

Built on a non combustible floor with at least 32" (81.3cm) surrounding the oven and at least 40" (101.6cm) in front of the oven

Minimum clearance under oven: 31 inches² (200cm²)

Leave enough clearance for someone to service the oven

Oven Weight			
Rotante47	4400lbs. (1995Kg)		
Rotante59	5300lbs. (2404Kg)		

Number of Pizzas				
Model	12" Pizzas			
Rotante47	6			
Rotante59	14			

BTU: Rotante47 - 92,500 BTU Rotante59 - 97,500 BTU

Electrical Information (60Hz)					
	Voltage	Phase	Hz	Amps	
Standard Voltage	208-240	3	60	19	

*Plus a dedicated neutral is required.



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249

Printed in U.S.A. REV 1 01/2017 LH-895