



PROJECT: _____
 ITEM # _____ QTY: _____
 MODEL # _____
 AIA # _____ SIS # _____

BLAST CHILLER / BLAST FREEZER / THAWING / RETARDER / SLOW COOKER / WARMER

BLAST CHILLER / BLAST FREEZER / THAWING / RETARDER / SLOW COOKER / WARMER

HI5-12-200U

EXCLUSIVE WARRANTY

- ▶ 3 Year Parts & Labor Warranty
- ▶ 5 Year Compressor Warranty
- ▶ Exclusive 2 Year Warranty On Magnetic Door Gaskets



CABINET CONSTRUCTION

- Stainless Steel Exterior And Interior
- Stay-Open Door Feature For Easy Product Loading
- Snap-In Magnetic Door Gaskets
- 7" Touch Capacitive IPS High Resolution Display
- Circuit Breaker For Compressor Protection
- Automatic Recognition Of Core Probe
- Multi Point Sensor Temperature Display Button
- Core Probe Heater Button
- Infinity Mode Program With Adjustable Set Point
- Automatic Conservation Mode At End Of Cycle

FEATURES

- Multi-Functional Unit Offers 5 Distinct Functions: Blast Chill, Blast Freezing, Thawing, Dough Retarder And Slow Cooking
- LCD Color Display For Precise Control Of Chilling And Cooking Cycles
- Cook/Chill Option With Probe Or Timer Setting
- Shock Freezing
- Core Probe Temperature Or Timed Cycle For Blast Chilling Or Shock Freezing
- HACCP Alarm Display Button
- Pre-Cooling Cycle Button
- Holds 99 Program Memory (68 factory pre-set and up to 31 custom programs)
- USB Data Recorder/Interface

REFRIGERATION

- Self-Contained Refrigeration System Utilizes R-404 Refrigerant
- Hot Gas Condensate Evaporator
- Adjustable Evaporator Fan Speed Button
- Timed Manual Defrost Button
- Temp Range 194°F /0°F



Please Verify Qualifying Units By Visiting:
www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- Printer Kit
- Removable Sterilizer
- Remote Condensing Unit
- Water Cooled Condenser
- 2" Casters With Brakes

3779 Champion Blvd, Winston-Salem, NC 27105




ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 9/26/23 Printed in U.S.A.

APPROVAL: _____ DATE: _____

HI5-12-200U



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

12" Top and 3" rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	59.43	Cabinet Voltage	208-240	Height	79"
Width, Overall (in.)	43 1/4"	Total Amperes	24.0	Width	47"
Depth, Overall (with handle)	42 1/4"	NEMA Plug	15-30P	Depth	38"
Height Overall (in.)	70 7/8"	REFRIGERATION DATA		Crated Weight	789 lbs
Depth, Door Open 90°	64 71/100"	Condensing Unit Size, HP	4	*NOTE: Remote unit are field wired and comes with 6" legs. Refrigerant must be specified at time of order.	
Door Opening (in.)	26 19/50" x 32 17/25"	Refrigerant	R-404		
Pan Capacity/Pan Size	12 / 18" x 26"	Capacity (BTU/HR) (100°F/20°F)	28615		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 9/26/23 Printed in U.S.A.

an Ali Group Company



The Spirit of Excellence