

PROJECT:		
ITEM #		OTY:
MODEL#		
AIA #	SIS #	
MM "	0.0 #	

PIZZA PREP TABLE WITH DRAWERS

VPPD72HC-3



EXCLUSIVE WARRANTY

- **6 Year Parts & Labor Warranty**
- 7 Year Compressor Warranty
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)











CABINET CONSTRUCTION

- · Stainless Steel Exterior (galvanized back and bottom)
- · Aluminum Interior
- · Hinged, Insulated, Removable Flat Lift-Up Lid
- One-Piece, Snap-In Magnetic Door/Drawer Gaskets
- · Heavy-Duty Aluminum Pan Liner
- · 8' Cord And Plug (see electrical data for details)

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- · Side Mounted Refrigeration System For Serviceability
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- · Epoxy Coated Evaporator Coil
- Refrigerator Capable Of Maintaining Product Temperature

FEATURES

- **Full Electronic Control**
- Chrome Lift Off Hinges
- Low Profile Horizontal Door/Drawer Handles
- Epoxy Coated Shelves (2 per section)
- Stay-Open Door/Drawer Feature For Easy Product Loading
- · Heavy-Duty Stainless Steel Drawer Frames
- · Heavy-Duty Pan Divider Supports Supplied
- · Locking Divider Bars (drawers only)
- Top Accommodates 6" Deep Food Service Pans (pans not included)
- Accommodates 6" Deep Full Size Food Service Pans In Both Upper And Lower Drawers (pans not included)
- Heavy-Duty, Telescoping Drawer Slides With Locking Mechanism
- 275 lbs Drawer Load Rating (per drawer)
- Removable 19" Wide Cutting Board
- · 3" Casters Two With Locks



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- · Stainless Steel Interior
- · Stainless Steel Back
- · Secure-Temp™ Technology
- · Exterior Door Laminate
- Door/Drawer Locks
- Additional Shelves
- · Shelf Clips
- · Single & Double Overshelf Kit
- · Bun Tray Rack (per door)
- · Tray Slide Kit

- · 6" Casters, 6" Legs Or 6" Seismic Legs
- · Compressor On Left (specify at time of order)
- Remote Models* (6" legs only)
 (refrigerant must be specified at time of order, see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105


ph: (888) 845-9800 fax: (800) 253-5168


APPROVAL: ___ Rev. 10/6/23 Printed in U.S.A.


__ DATE: __



VPPD72HC-3







We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS		
Net Capacity (cubic ft.)	22.77	Cabinet Voltage	115/60/1	Height	48"	
Width, Overall (in.)	72 1/8"	Total Amperes	4.5	Width	75"	
Depth, Overall (with cutting board)	37"	NEMA Plug (8' cord)	5-15P	Depth	45"	
Height Overall (with casters)	53 3/8"	REFRIGERATION DATA		Crated Weight	554 lbs	
Depth, Drawer Extended	55 7/8"	Condensing Unit Size, HP	1/2			
Depth, Door Open 90°	55 1/4"	Refrigerant*	R-290	*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.		
Drawer Openings (in.)	21 5/8" x 6 1/2"	Capacity (BTU/HR) (100°F/20°F)	2940			
Door Opening (in.)	21 5/8" x 23 5/8"	Heat Rejection (BTU/HR)	4410			
No. Of Doors/Shelves/Drawers	1/2/3	Charge (lbs/grams)	0.231/105			
Required Clearance: 3" Bottom & 2" Rear						

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 10/6/23 Printed in U.S.A.

