

Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

HORIZON TOP MOUNT REACH-IN

HF2HC Glass Double Door Reach-In Freezer

Hydrocarbon Series

MODEL: HF2HC-1G



5 Year Parts/Labor Warranty Available 7 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior is stainless steel front and continuous coil coated sides
- Interior liner is made of corrosion resistant aluminum
- Full electronic control
- Expansion valve technology
- One-piece grille
- LED interior light
- Self-closing door with 120° stay-open feature, on cam-lift hinges
- Snap-in magnetic gaskets for positive door seal
- Six (6) heavy-duty epoxy coated wire shelves
- 6" Heavy-duty casters, two (2) with brakes
- 8' Cord and plug (see electrical data for details)

OPTIONS & ACCESSORIES

- 3 Year parts/labor standard, additional 2 year warranty available
- Tray slide pair, 1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (A)
- Stainless steel universal tray slide pair,1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (AC)
- Tray slide kit #4 (19 sets per half section)
- · Additional epoxy shelves
- · Shelf clips
- Door locks
- Stainless steel breaker
- 6" Legs seismic/flanged
- 3" Casters
- Remote option* (see note on back page)

FINISH OPTIONS

HF Standard

(S/S front, continuous coil coated sides, aluminum interior)

(S/S front, S/S sides, aluminum interior)

- (S/S front, continuous coil coated sides, S/S interior)

(Complete S/S exterior & interior)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE &
- Hot gas condensate evaporator
- Adaptive defrost
- · Epoxy coated evaporator coil
- Freezer capable of maintaining product temperature down to -10°F










3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	HF2HC-1G	
EXTERNAL DIMENSIONAL DATA		
Width Overall	52"	
Depth Overall with Handle	33 %"	
Height Overall	85"	
Number of Doors	2	
Depth with Door Open 90°	55 ½"	
Door Openings (in)	21 %" x 61 %"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	46.29	
Internal Width Overall (in)	48"	
Internal Depth Overall (in)	25 ⅓"	
Internal Height Overall (in)	62"	
Number of Shelves	6	
ELECTRICAL DATA		
Full Load Amperes 115/60/1	13.2	
REFRIGERATION DATA		
Horsepower	(2) 3/4	
Capacity (BTU/Hr)	3854	
Heat Rejection (BTU/Hr)	5781	
Charge (lbs/grams)	0.2535/115	
SHIPPING DATA		
Gross Weight - Crated	596 lbs	
Height - Crated	88"	
Width - Crated	55"	
Depth - Crated	36"	

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

Top Mount Reach-In Freezer Model: HF2HC-1G





ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.